

22"

HIGH VELOCITY FAN



STANDARD
YM - YOKE MOUNT

ADDITIONAL MOUNTING OPTIONS:



RM Rack Mount
57 lbs



CW Column-Wall
62 lbs



PS Portable Stroller
85 lbs



PB Pedestal Base
61 lbs

SHIPPING WEIGHT:

SIZE	CFM	HP	FAN DIMENSIONS			AIR THROW DISTANCE	SHIPPING WEIGHT
			W	D	ID		
22"	5570	1/2	29"	16"	22.5"	100'	49 lbs

FEATURES

- Propeller:** 21" Diameter, 3 Blade GalvAlum, 19°
- Fan Inlet/Outlet:** High Impact Polypropylene
- Finger Guards:** OSHA Compliant, Spiral Wound Steel
- Power Cord (115V Only):** 12' Length (Switch Optional)
- RPM:** 1725
- Decibels:** 66.5 @ 20' - 77.6 @ 3'
- Coverage:** 3600 ft²


Warranty: 2 Years

MOTOR

VOLTAGE	MOTOR AMPS	RUNNING AMPS
115V/208-230V*	6.0/3.0-2.9	5.9/2.9-2.8
208-230/460V	2.4-2.3/1.2	2.3-2.2/1.1
277V	1.85	1.75

- Enclosure:** TEAO Standard
- Frame:** 56
- Ambient Temperature:** 104°F
- Duty Cycle:** Continuous

*standard



AIR FLOW PATTERN

Above velocities shown in feet/minute.