



FL-Series Foundationless Floor Mounted Jib Crane 1/8 Ton Capacity

Capacity (Pounds)	Model	Hub	Span	Beam Height	Flange Width	Base Diameter	Unit Weight
250	FL2586	8'	6'	6"	3-3/8"	26"	375#
250	FL2588	8'	8'	6"	3-3/8"	26"	405#
250	FL25810	8'	10'	6"	3-3/8"	26"	425#
250	FL25812	8'	12'	6"	3-3/8"	26"	565#
250	FL25814	8'	14'	8"	4"	26"	690#
250	FL25106	10'	6'	6"	3-3/8"	26"	410#
250	FL25108	10'	8'	6"	3-3/8"	26"	440#
250	FL251010	10'	10'	6"	3-3/8"	26"	455#
250	FL251012	10'	12'	6"	3-3/8"	26"	620#
250	FL251014	10'	14'	8"	4"	26"	730#
250	FL25126	12'	6'	6"	3-3/8"	26"	460#
250	FL25128	12'	8'	6"	3-3/8"	26"	475#
250	FL251210	12'	10'	6"	3-3/8"	26"	495#
250	FL251212	12'	12'	6"	3-3/8"	26"	665#
250	FL251214	12'	14'	8"	4"	26"	780#

NOTE:

- Existing concrete must be a minimum of 6" thick reinforced with a minimum 3,000 psi (5 bag mix), soil pressure must support 2,500 psi.
- Concrete in and around the area (6' x 6') of the base plate must be free of cracks and must appear in good condition.
- All units have 26" diameter base and 22" bolt circle 6 holes 1-1/4" diameter.
- All foundations should be checked by a structural engineer.

Options: Tagline Kits

Epoxy Anchor Kits

Rotation Stops

Bolt Pattern Templates

Outdoor Applications & Stainless Steel

Hoists & Trolleys

